


RT Ultra

- + Designed for heavy duty applications and large components
- + Thermal Core Technology for optimized heat transfer
- + MIL-SPEC / IPC standard



CHISEL




For use with




Model		Watt	Soldering Iron	Safety Rests	Length (mm) (inch.)	a / b (mm) (inch.)	Order No.
RTU 015 S MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	28.0 1.102	1.5 / 0.4 0.059 / 0.016	T0050105899
RTU 022 S MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	28.0 1.102	2.2 / 0.6 0.087 / 0.024	T0050105999
RTU 032 S MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	27.5 1.083	3.2 / 0.8 0.126 / 0.031	T0050106099
RTU 032 S L MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	34.0 1.339	3.2 / 0.8 0.126 / 0.031	T0050106199
RTU 050 S MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	27.5 1.083	5.0 / 1.2 0.197 / 0.047	T0050106299
RTU 076 S MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	28.0 1.102	7.6 / 1.5 0.299 / 0.059	T0050106399
RTU 093 S MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	28.0 1.102	9.3 / 2.0 0.366 / 0.079	T0050106499

BEVEL CUT



Model		Watt	Soldering Iron	Safety Rests	Length (mm) (inch.)	a / b (mm) (inch.)	Order No.
RTU 020 B MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	29.0 1.142	2.0 0.079	T0050105599
RTU 035 B MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	29.0 1.142	3.5 0.138	T0050105699
RTU 050 B MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	30.0 1.181	5.0 0.197	T0050105799

CONICAL




Model		Watt	Soldering Iron	Safety Rests	Length (mm) (inch.)	a / b (mm) (inch.)	Order No.
RTU 004 C MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	27.5 1.083	0.4 0.016	T0050104999
RTU 008 C MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	29.0 1.142	0.8 0.031	T0050105099
RTU 016 C MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	27.5 1.083	1.6 0.063	T0050105199

SOLDERING IRON

WXUP MS
150 W
T0052923099



Heating up time




*from 50°C to 350°C / 120°F to 620°F



Component size



GULLWING



Model		Watt	Soldering Iron	Safety Rests	Length (mm) (inch.)	a / b (mm) (inch.)	Order No.
RTU 020 G MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	28.0 1.102	2.0 / 1.3 0.079 / 0.051	T0050106599

BLADE



Model		Watt	Soldering Iron	Safety Rests	Length (mm) (inch.)	a / b (mm) (inch.)	Order No.
RTU 100 K MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	27.0 1.063	10.0 / 1.5 0.394 / 0.059	T0050106699
RTU 160 K MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	27.0 1.063	16.0 / 1.5 0.630 / 0.059	T0050106799
RTU 200 K MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	27.0 1.063	20.0 / 1.5 0.787 / 0.059	T0050106899
RTU 330 K MS	MIL-SPEC VERSION AVAILABLE	150	WXUP MS	WSR 200	27.0 1.063	33.0 / 1.5 1.299 / 0.059	T0050106999

Make no compromise in high-end soldering.
Find your perfect RT Ultra tips here:
www.weller-tools.com/nocompromise