Wafer tweezers

Suitable for 3" to 6" wafers

> Serrated finger grips for

| Secure handling Wafer tweezers are available to order in various sizes and coatings | | steel, non-magnetic, non-rusting, acid-proof, heat-resistant | | | | sting, | |
|--|--------|--|----|------|-----|-------------------------------|---|
| | | | | | | | s = Paddle width s = Paddle depth |
| 4.921 Inch / 125 mm | Model | Weight | | А | В | Material | Description |
| | | oz. | g | mm | mm | | |
| | 91SA | 0.53 | 15 | 12 | 7 | Special stainless steel | Standard wafer tweezers for 3" and 4" wafers. |
| 5.118 Inch / 130 mm | Model | Weight | | А | В | Material | Description |
| | | oz. | g | mm | mm | | |
| No. of Contract of | 608ASA | 0.81 | 23 | 30 | 8.5 | Special stainless steel | Wafer tweezers with flat lower paddle and 6 upper fingers for protecting wafers against damage. For 6" wafers. Model same as 600ASA, but 30 mm/1.181 Inch wide. |
| - | 600ASA | 0.81 | 23 | 19.5 | 8 | Special stainless steel | Wafer tweezers with flat lower paddle and 6 upper fingers for protecting wafers against damage. For 6" wafers. |
| 5.906 Inch / 150 mm | Model | Weight | | А | В | Material | Description |
| | | OZ. | g | mm | mm | | |
| 1 | 141SAP | 1.06 | 30 | 30 | 8 | Special stainless steel | Wafer tweezers, 150 mm with polyester tips for protecting Si, GaAs or Ti wafers against damage. For 4" - 6" wafers. |

For all models with the suffix SA in the order number: Special stainless

Side Cutters and Tip Cutters



Kits